INSTYTUT TECHNIKI BUDOWLANEJ
PL 00-611 WARSZAWA
ul. Filtrowa 1
tel.: (+48 22) 825-04-71
(+48 22) 825-76-55
fax: (+48 22) 825-52-86
www.itb.pl

Designated according to Article 29 of Regulation (EU) No 305/2011 and member of EOTA (European Organisation for Technical Assessment)

Member of EOTA
www.eota.eu

European Technical Assessment

ETA-16/0739 of 30/03/2021

General part

Technical Assessment Body issuing the European Technical Assessment	Instytut Techniki Budowlanej
Trade name of the construction product	ESDS, EFS, EVFS, ESTS
Product family to which the construction product belongs	Fastening screws for metal members and sheeting
Manufacturer	Van Roij Fasteners Europe B.V. Jan Tooropstraat 16 5753 DK Deurne, Netherlands
Manufacturing plant(s)	Van Roij Fasteners Europe B.V. plants
This European Technical Assessment contains	136 pages including 131 Annexes which form an integral part of this Assessment
This European Technical Assessment is issued in accordance with regulation (EU) No 305/2011, on the basis of	European Assessment Document (EAD) 330046-01-0602 “Fastening screws for metal members and sheeting”
This version replaces	ETA-16/0739 issued on 30/06/2020

This European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction has to be identified as such.

Specific Part

1. Technical description of the product

The fastening screws ESDS, EFS, EVFS and ESTS are the self-drilling and self-tapping screws listed in Table 1. The fastening screws are partly supplied with a metallic washer and an EPDM sealing ring. Some screws can be completed with saddle washers ESW. For details see the Annexes 1 to 130.

The fastening screw and the corresponding connections are subject to tension and shear forces.

Table 1

No.	Screw	Material	Annex
1	ESDS-0-Z 4.8xL	galvanized carbon steel with ≥ 12 µm of zinc coating	1, 4
2	ESDS-0-P 4.8xL	galvanized carbon steel with PREMIUM coating	2, 5
3	ESDS-0-SP 4.8xL	galvanized carbon steel with SUPER PREMIUM coating	3, 6
4	ESDS-0-B 4.8xL	stainless steel (bi-metal)	7, 8
5	ESDS-PH-0-Z 4.8xL	galvanized carbon steel with ≥ 12 µm of zinc coating	9
6	ESDS-PH-0-P 4.8xL	galvanized carbon steel with PREMIUM coating	10
7	ESDS-PH-0-B 4.8xL	stainless steel (bi-metal)	11, 12
8	ESDS-PH-0-B 5.5xL	stainless steel (bi-metal)	13
9	ESDS-0-B 6.3xL	stainless steel (bi-metal)	14
10	EFS-2-Z 4.8xL	galvanized carbon steel with ≥ 12 µm of zinc coating	15
11	EFS-2-P 4.8xL	galvanized carbon steel with PREMIUM coating	16
12	EFS-2-SP 4.8xL	galvanized carbon steel with SUPER PREMIUM coating	17
13	EFS-2-B 4.8xL	stainless steel (bi-metal)	18
14	EFS-PH-2-Z 4.8xL	galvanized carbon steel with ≥ 12 µm of zinc coating	19
15	EFS-PH-2-P 4.8xL	galvanized carbon steel with PREMIUM coating	20
16	ESDS-3-Z 4.8xL	galvanized carbon steel with ≥ 12 µm of zinc coating	21, 24, 27, 30
17	ESDS-3-P 4.8xL	galvanized carbon steel with PREMIUM coating	22, 25, 28, 31
18	ESDS-3-SP 4.8xL	galvanized carbon steel with SUPER PREMIUM coating	23, 26, 29, 32
19	ESDS-3-B 4.8xL	stainless steel (bi-metal)	33, 34, 35, 36
20	ESDS-3-B 5.5xL	stainless steel (bi-metal)	37, 38, 39, 40, 41
21	EVFS-3-B 5.5xL	stainless steel (bi-metal)	42, 43
22	ESDS-PH-3-Z 4.8xL	galvanized carbon steel with ≥ 12 µm of zinc coating	44
23	ESDS-PH-3-P 4.8xL	galvanized carbon steel with PREMIUM coating	45
24	ESDS-5-Z 5.5xL	galvanized carbon steel with ≥ 12 µm of zinc coating	46, 49, 52, 55
25	ESDS-5-P 5.5xL	galvanized carbon steel with PREMIUM coating	47, 50, 53, 56
26	ESDS-5-SP 5.5xL	galvanized carbon steel with SUPER PREMIUM coating	48, 51, 54, 57
27	ESDS-5-B 5.5xL	stainless steel (bi-metal)	58, 59, 60, 61
28	ESDS-PH-5-B 5.5xL	stainless steel (bi-metal)	62
29	ESDS-PH-5-Z 5.5xL	galvanized carbon steel with ≥ 12 µm of zinc coating	63
30	ESDS-PH-5-P 5.5xL	galvanized carbon steel with PREMIUM coating	64
31	ESDS-6-Z 6.3xL	galvanized carbon steel with ≥ 12 µm of zinc coating	65, 68, 71
32	ESDS-6-P 6.3xL	galvanized carbon steel with PREMIUM coating	66, 69, 72
33	ESDS-6-SP 6.3xL	galvanized carbon steel with SUPER PREMIUM coating	67, 70, 73
34	ESDS-PH-6-B 6.3xL	stainless steel (bi-metal)	74
35	ESDS-8-Z 5.5xL	galvanized carbon steel with ≥ 12 µm of zinc coating	75, 78, 81, 84
36	ESDS-8-P 5.5xL	galvanized carbon steel with PREMIUM coating	76, 79, 82, 85
37	ESDS-8-SP 5.5xL	galvanized carbon steel with SUPER PREMIUM coating	77, 80, 83, 86
38	ESDS-12-Z 5.5xL	galvanized carbon steel with ≥ 12 µm of zinc coating	87, 90, 93, 96

Table 1, cont.

39	ESDS-12-P 5.5xL	galvanized carbon steel with PREMIUM coating	88, 91, 94, 97
40	ESDS-12-SP 5.5xL	galvanized carbon steel with SUPER PREMIUM coating	89, 92, 95, 98
41	ESDS-12-B 5.5xL	stainless steel (bi-metal)	99, 100, 101, 102
42	ESDS-20-Z 5.5xL	galvanized carbon steel with ≥ 12 µm of zinc coating	103, 106, 109, 112
43	ESDS-20-P 5.5xL	galvanized carbon steel with PREMIUM coating	104, 107, 110, 113
44	ESDS-20-SP 5.5xL	galvanized carbon steel with SUPER PREMIUM coating	105, 108, 111, 114
45	ESTS-0A-Z 6.5xL	galvanized carbon steel with ≥ 12 µm of zinc coating	115, 116, 117, 118
46	ESTS-0A-S 6.5xL	galvanized stainless steel	119, 120, 121, 122
47	ESTS-0B-Z 6.3xL	galvanized carbon steel with ≥ 12 µm of zinc coating	123, 125
48	ESTS-0B-P 6.3xL	galvanized carbon steel with PREMIUM coating	124, 126
49	ESTS-WH-0-Z 4.2xL	galvanized carbon steel with ≥ 8 µm of zinc coating	127
50	ESTS-WH-0-P 4.2xL	galvanized carbon steel with PREMIUM coating	128
51	ESDS-WH-2-Z 4.2xL	galvanized carbon steel with ≥ 8 µm of zinc coating	129
52	ESDS-WH-2-P 4.2xL	galvanized carbon steel with PREMIUM coating	130

2. Specification of the intended use in accordance with the applicable European Assessment Document (EAD)

The fastening screws are intended to be used for fastening steel sheeting to steel, aluminum or timber supporting substructures. For details see the Annexes 1 to 130. The component to be fastened is component I and the supporting structure is component II. The sheeting can either be used as wall or roof cladding or as load bearing wall and roof element. The fastening screws can also be used for the fastening of any other thin gauge metal members.

The intended use comprises fastening screws and connections for indoor and outdoor applications. Fastening screws which are intended to be used in external environments with ≥ C2 corrosion according to the standard EN ISO 12944-2 are made of stainless steel.

Furthermore the intended use comprises connections with predominantly static loads (e.g. wind loads, dead loads).

The provisions made in this European Technical Assessment are based on an assumed working life of the fasteners of 25 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer or Technical Assessment Body, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3. Performances of the product and references to the methods used for their assessment

3.1. Performance of the product

3.1.1 Mechanical resistance and stability (BWR 1)

The characteristic values of the shear resistance of connections and tension resistance of connections with the fasteners are given in Annex 1 to 130. The values were determined by tests according to EAD 330046-01-0602.

The design values shall be determined according to Annex 131 and EAD 330046-01-0602.

For the corrosion protection the rules given in EN 1993-1-3, EN 1993-1-4 and EN 1999-1-4 shall be taken into account. Fastening screw which are made of stainless steel are intended to be used in external environments ≥ C2 corrosion according to the standard EN ISO 12944-2.

3.1.2. Safety in case of fire (BWR 2)

The fastening screws are considered to satisfy the requirements of performance class A1 of reaction to fire, in accordance with the provisions of the EC Decision 96/603/EC (as amended) without the need for testing on the basis of its listing in that decision.

3.2. Methods used for the assessment

The assessment of products has been made in accordance with the EAD 330046-01-0602.

4. Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

According to Decision 1998/214/EC, amended by 2001/596/EC, of the European Commission the system 2+ of assessment and verification of constancy of performance applies (see Annex V to regulation (EU) No 305/2011).

5. Technical details necessary for the implementation of the AVCP system, as provided for in the applicable European Assessment Document (EAD)

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited at the Instytut Techniki Budowlanej.

For type testing the results of the tests performed as part of the assessment for the European Technical Assessment shall be used unless there are changes in the production line or plant. In such cases the necessary type testing has to be agreed between Instytut Techniki Budowlanej and the notified body.

Issued in Warsaw on 30/03/2021 by Instytut Techniki Budowlanej


Anna Panek, MSc
Deputy Director of ITB

Materials

Fastener:	carbon steel – SAE1022, quenched, tempered and coated: galvanized with PREMIUM coating
Washer:	A16 – aluminum washer with EPDM ring
Component I:	S280GD, S320GD or S350GD – EN 10326
Component II:	S235 – S355 EN 10025-1
Drilling capacity:	$\Sigma ti \leq 12{,}00$ mm

Timber substructures

No performance assessed



$t_{N,II}$ [mm]		4,00	5,00	6,00	8,00	10,00	Wood class ≥ C24
$M_{t,nom}$		5 Nm					
$V_{R,k}$ [kN] for $t_{N,I}$ [mm]	0,50	1,66	1,66	1,66	1,66	1,66	
	0,55	1,66	1,66	1,66	1,66	1,66	
	0,60	1,66	1,66	1,66	1,66	1,66	
	0,63	1,76	1,76	1,76	1,76	1,76	
	0,70	1,76	1,76	1,76	1,76	1,76	
	0,75	2,60	2,60	2,60	2,60	2,60	
	0,80	2,60	2,60	2,60	2,60	2,60	
	0,88	2,60	2,60	2,60	2,60	2,60	
	1,00	3,37	3,37	3,37	3,37	3,37	
	1,13	3,37	3,37	3,37	3,37	3,37	
	1,15	3,37	3,37	3,37	3,37	3,37	
	1,25	3,37	3,37	3,37	3,37	3,37	
	1,50	3,37	3,37	3,37	3,37	3,37	
	1,75	3,37	3,37	3,37	3,37	3,37	
	2,00	3,37	3,37	3,37	3,37	3,37	
$N_{R,k}$ [kN] for $t_{N,I}$ [mm]	0,50	2,53	2,53	2,53	2,53	2,53	
	0,55	2,53	2,53	2,53	2,53	2,53	
	0,60	2,77	2,77	2,77	2,77	2,77	
	0,63	2,77	2,77	2,77	2,77	2,77	
	0,70	2,89	2,89	2,89	2,89	2,89	
	0,75	2,89	2,89	2,89	2,89	2,89	
	0,80	2,89	2,89	2,89	2,89	2,89	
	0,88	2,89	2,89	2,89	2,89	2,89	
	1,00	4,27	4,27	4,27	4,27	4,27	
	1,13	4,27	4,27	4,27	4,27	4,27	
	1,15	4,27	4,27	4,27	4,27	4,27	
	1,25	4,27	4,27	4,27	4,27	4,27	
	1,50	4,27	4,27	4,27	4,27	4,27	
	1,75	4,27	4,27	4,27	4,27	4,27	
	2,00	4,27	4,27	4,27	4,27	4,27	

If both components I and II are made of S320GD the values $V_{R,k}$ may be increased by 8,3%
If both components I and II are made of S350GD the values $V_{R,k}$ may be increased by 16,6%

Fastening screws for metal members and sheeting

Self-drilling screws ESDS-12-P 5.5xL
with hexagon head and washer A16

Annex 94


of European Technical Assessment ETA-16/0739

Materials

Fastener:	carbon steel – SAE1022, quenched, tempered and coated: galvanized with PREMIUM coating
Washer:	-
Component I:	S280GD, S320GD or S350GD – EN 10326
Component II:	S235 – S355 EN 10025-1
Drilling capacity:	$\Sigma t_i \leq 12{,}00$ mm

Timber substructures

No performance assessed



$t_{N,II}$ [mm]		4,00	5,00	6,00	8,00	10,00	Wood class ≥ C24
$M_{t,nom}$		5 Nm					
$V_{R,k}$ [kN] for $t_{N,I}$ [mm]	0,50	1,66	1,66	1,66	1,66	1,66	
	0,55	1,66	1,66	1,66	1,66	1,66	
	0,60	1,66	1,66	1,66	1,66	1,66	
	0,63	1,76	1,76	1,76	1,76	1,76	
	0,70	1,76	1,76	1,76	1,76	1,76	
	0,75	2,60	2,60	2,60	2,60	2,60	
	0,80	2,60	2,60	2,60	2,60	2,60	
	0,88	2,60	2,60	2,60	2,60	2,60	
	1,00	3,37	3,37	3,37	3,37	3,37	
	1,13	3,37	3,37	3,37	3,37	3,37	
	1,15	3,37	3,37	3,37	3,37	3,37	
	1,25	3,37	3,37	3,37	3,37	3,37	
	1,50	3,37	3,37	3,37	3,37	3,37	
	1,75	3,37	3,37	3,37	3,37	3,37	
	2,00	3,37	3,37	3,37	3,37	3,37	
$N_{R,k}$ [kN] for $t_{N,I}$ [mm]	0,50	0,80	0,80	0,80	0,80	0,80	
	0,55	0,80	0,80	0,80	0,80	0,80	
	0,60	0,80	0,80	0,80	0,80	0,80	
	0,63	1,00	1,00	1,00	1,00	1,00	
	0,70	1,00	1,00	1,00	1,00	1,00	
	0,75	1,31	1,31	1,31	1,31	1,31	
	0,80	1,31	1,31	1,31	1,31	1,31	
	0,88	1,31	1,31	1,31	1,31	1,31	
	1,00	1,31	1,31	1,31	1,31	1,31	
	1,13	1,31	1,31	1,31	1,31	1,31	
	1,15	1,31	1,31	1,31	1,31	1,31	
	1,25	1,31	1,31	1,31	1,31	1,31	
	1,50	1,31	1,31	1,31	1,31	1,31	
	1,75	1,31	1,31	1,31	1,31	1,31	
	2,00	1,31	1,31	1,31	1,31	1,31	

If both components I and II are made of S320GD the values $V_{R,k}$ may be increased by 8,3%
If both components I and II are made of S350GD the values $V_{R,k}$ may be increased by 16,6%

Fastening screws for metal members and sheeting	**Annex 88**
Self-drilling screws ESDS-12-P 5.5xL with hexagon head	of European Technical Assessment ETA-16/0739