
FIJAMOS EL MUNDO

02183T48 i-FYT Tx3 4,8

Material	AISI 304 stainless steel		Diameter (mm)	4,8
Heat treatment	Austenitising + quenching + tempering		Drilling capacity	3 mm aluminium
Corrosion protection	Stainless steel	Hardness	Surface	194 HV
Lengths (mm)	25		Core	194 HV
Shear failure load	6.300 N		Tensile failure load	7.300 N



Maximum pull-out force in aluminium (N)*

Thickness (mm)	2 x 1,00	3,00
Force (N)	1.230	2.118

*. Mean test value.




Maximum pull-over force (N)*

Thickness (mm)	0,50	0,60	0,70	0,80	1,00
Without washer (N)	840	1.008	1.176	1.344	1.680
P 16 washer (N)	1.120	1.344	1.568	1.792	2.240
P 18 washer (N)	1.260	1.512	1.764	2.016	2.520

*. Values obtained from the Spanish structural steel code for an ST37 sheet (350 N/mm2)







Maximum shear force (N)

Thickness (mm)	1,00	1,50	2,00
Section (mm)	1,00	1,50	2,00
Force (N)	2.068	3.102	4.136

*. Values obtained from the Spanish structural steel code for an ST37 sheet (350 N/mm2)

www.faytexsl.com
C/ Palier, 19 · 28914 Leganés (Madrid) Spain
+34 916 945 561

Translation of the Spanish version; it may contain errors.

FIJAMOS EL MUNDO

The values in table 1 are mean test values (ẋ). The following factors are recommended according to CEN/TS 17659:

Table 2 - Recommended material partial (safety) factors for fastening in structural decks of different marterials

Material of structural deck	Nominal thickness	Characteristics [a]	γM
Steel according to EN 10346	0,50 ≤ t < 0,70 mm	yield strength ≥ 280 N/mm^2	2,0
	t ≥ 0,70 mm	yield strength ≥ 280 N/mm^2	1,8
Aluminium according to EN 485	t ≥ 0,70 mm	yield strength ≥ 195 N/mm^2	2,0 [b]
Concrete according to EN 206		Minimum C12/15	2,1 [c]
Light weight concrete according to EN 12602		≥ 500 kg/m^3	3,0 [b]

Material of structural deck	Nominal thickness	Characteristics [a]	γM
Wood - soft wood according to EN 338	t ≥ 20 mm	Minimum C24	1,86 [d]
OSB according to EN 300	t ≥ 18 mm	Minimum OSC/3	1,86 [d]
Plywood according to EN 636	t ≥ 18 mm	Minimum Service class 2 (EN 1995-1-1) Intended application = Structural S	1,86 [d]

a. Recommended for new structural decks.
b. This recommended value is based on hnowledge / experience.
c. This value is based on γ_{inst} = 1,4.
d. γM is the total safety based on κ_{mod} = 0,7 according EC 5.

Example of fastener strength calculation:

Data: Steel purlin 8 mm / Sheet 0,6 mm / i-FYT Tx3 4,8 with washer 16



1. Tensile strength:

- From the data sheet values:
  - Wtest = 16.000 N/fastener
- Apply 90% reduction factor:
  - Wchar = 14.400 N/fastener
- Apply safety factor:
  - Wadm = 8.000 N/fastener

2. Pull-over resistance:

- From the data sheet values:
  - Wadm = 1.344 N/fastener

The lower of these values is used

Design value of the fasteners: Wadm = 1.344 N/fastener.

A1 REACCIÓN AL FUEGO — Fire protection
A2 — AISI 304
ALU — Drills Aluminium
Screw Self-drilling
Head Torx
TÜV NORD PN-EN ISO 9001

Stainless

www.faytexsl.com
C/ Palier, 19 · 28914 Leganés (Madrid) Spain
+34 916 945 561

Translation of the Spanish version; it may contain errors.