Translation of the Spanish version; it may contain errors. The Spanish version prevails.

DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) No 305/2011 (Construction Products Regulation)

No.: FYT-02100163

1-	Unique identification code of the product-type:	02100163
2-	Identification of the construction product:	See product label
3-	Intended use of the product:	Fixing steel sections to timber structural members.
4-	Manufacturer's name and contact address	Fijaciones FYT, S.L. C/ Palier, 19 28914 Leganés (Madrid) Spain
5-	System of assessment and verification of constancy of performance of the product as set out in Annex V	4
6-	European Technical Assessment name and number	Not applicable

7- Declared performance

Essential characteristics	Performance	Technical specifications
Ultimate tensile load	See Annex 1	-
Ultimate shear load	See Annex 1	-
Pull-out force in aluminium	See Annex 1	-
Material	Stainless steel	AISI-304

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Enrique Capilla, Technical Director

Leganés, 23 March 2020

Faytex, S.L./Fijaciones FYT, S.L.
C/ Palier, 19 28914 Leganés (Madrid) Spain
Tel: +34916945561/+34916942861
E-Mails: empresa@faytexsl.com / empresa@fyt.es
Web: www.faytexsl.com / www.fyt.es

Annex 1: Product data sheet

Stainless

02100163 i-FYT RCH MAD 6,3

Material	AISI 304 stainless steel	Diameter (mm)	6,3
Heat treatment	Austenitising + quenching + tempering	Drilling capacity	-
Corrosion protection	Stainless steel	Hardness – Surface	-
Lengths (mm)	20 - 260	Hardness – Core	-
Shear failure load	12.500 N	Tensile failure load	16.000 N

Maximum pull-out force (N)*

Thickness (mm)	25	30	40	50	70
Hole Ø (mm)	4,00	4,00	4,00	4,00	4,00
Force (N)	2.320	3.360	4.170	5.720	9.150

*. Mean test value.

Head
Hexagonal
10 mm





Maximum pull-over force (N)*

Thickness (mm)	0,50	0,60	0,70	0,80	1,00
Without washer (N)	840	1.008	1.176	1.344	1.680
P 16 washer (N)	1.120	1.344	1.568	1.792	2.240
P 18 washer (N)	1.260	1.512	1.764	2.016	2.520

*. Values obtained from the Spanish structural steel code for an ST37 sheet (350 N/mm2)

Maximum shear force (N)

Thickness (mm)	0,5	0,6	0,7	0,8	1,00	1,20
Section (mm)	25	25	25	25	25	25
Force (N)	795	1.045	1.317	1.609	3.704	4.445

*. Values obtained from the Spanish structural steel code for an ST37 sheet (350 N/mm2)

Stainless

www.faytexsl.com · C/ Palier, 19 · 28914 Leganés (Madrid) Spain · +34 916 945 561

Translation of the Spanish version; it may contain errors.

Faytex, S.L./Fijaciones FYT, S.L.
C/ Palier, 19 28914 Leganés (Madrid) Spain
Tel: +34916945561/+34916942861
E-Mails: empresa@faytexsl.com / empresa@fyt.es
Web: www.faytexsl.com / www.fyt.es