Translation of the Spanish version; it may contain errors. The Spanish version prevails.

DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) No 305/2011 (Construction Products Regulation)

No.: FYT-02113048

1- Unique identification code of the product-type:	02113048
2- Identification of the construction product:	See product label
3- Intended use of the product:	Drilling and fixing aluminium sections up to a total thickness of 4 mm.
4- Manufacturer's name and contact address	Fijaciones FYT, S.L. C/ Palier, 19 28914 Leganés (Madrid) Spain
5- Name and contact address of the authorised representative	Not applicable
6- System of assessment and verification of constancy of performance of the product as set out in Annex V	4
7- Name and identification number of the notified body	Not applicable
8- European Technical Assessment name and number	Not applicable

9- Declared performance

Essential characteristics	Performance	Technical specifications
Dimensions and tolerance	According to technical specifications	DIN 7504K
Ultimate tensile load	See Annex 1	-
Ultimate shear load	See Annex 1	-
Pull-out force in aluminium	See Annex 1	-
Material	Stainless steel	AISI-304
Drilling capacity (aluminium)	4 mm.	-

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Enrique Capilla, Technical Director
/
Leganés, 19 November 2026

Annex 1: Product data sheet

Stainless

02113048 i-FYT DK3 4,8

Material	AISI 304 stainless steel	Diameter (mm)	4,8
Heat treatment	Not hardened	Drilling capacity	4 mm aluminium
Corrosion protection	Stainless steel	Hardness – Surface	-
Lengths (mm)	19	Hardness – Core	-
Shear failure load	000 N	Tensile failure load	000 N

Maximum pull-out force in aluminium (N)*

Thickness (mm)	2,00	3,00	4,00
Force (N)	12.230	2.118	2.878**

*. Mean test value. **. Failure by fracture

Maximum pull-over force (N)*

Thickness (mm)	0,50	0,60	0,70	0,80	1,00
Without washer (N)	840	1.008	1.176	1.344	1.680
P 16 washer (N)	1.120	1.344	1.568	1.792	2.240
P 18 washer (N)	1.260	1.512	1.764	2.016	2.520

*. Values obtained from the Spanish structural steel code for an ST37 sheet (350 N/mm2)





Maximum shear force (N)

Thickness (mm)	1,00	1,50	2,00
Section (mm)	1,00	1,50	2,00
Force (N)	2.068	3.102	4.136

*. Values obtained from the Spanish structural steel code for an ST37 sheet (350 N/mm2)

Stainless

www.faytexsl.com C/ Palier, 19 · 28914 Leganés (Madrid) Spain +34 916 945 561

Translation of the Spanish version; it may contain errors.

Faytex, S.L./Fijaciones FYT, S.L.
C/ Palier, 19 28914 Leganés (Madrid) Spain
Tel: +34916945561/+34916942861
E-Mails: empresa@faytexsl.com / empresa@fyt.es
Web: www.faytexsl.com / www.fyt.es