*Translation of the Spanish version; it may contain errors. The Spanish version prevails.*

# DECLARATION OF PERFORMANCE

**In accordance with Annex III of Regulation (EU) No 305/2011 (Construction Products Regulation)**

**No.: FYT-02163N42**

| | |
|---|---|
| 1- Unique identification code of the product-type: | 02163N42 |
| 2- Identification of the construction product: | See product label |
| 3- Intended use of the product: | Drilling and fixing aluminium sections up to a total thickness of 3.5 mm. |
| 4- Manufacturer's name and contact address | Fijaciones FYT, S.L.<br>C/ Palier, 19<br>28914 Leganés (Madrid) Spain |
| 5- System of assessment and verification of constancy of performance of the product as set out in Annex V | 4 |
| 6- European Technical Assessment name and number | Not applicable |

7- Declared performance

| Essential characteristics | Performance | Technical specifications |
|---|---|---|
| Ultimate tensile load | See Annex 1 | - |
| Ultimate shear load | See Annex 1 | - |
| Pull-out force in aluminium | See Annex 1 | - |
| Material | Stainless steel | AISI-304 |
| Drilling capacity (aluminium) | 3,5 mm. | - |

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Enrique Capilla, Technical Director

Leganés, 23 March 2020

**Faytex, S.L./Fijaciones FYT, S.L.**
C/ Palier, 19 28914 Leganés (Madrid) Spain
Tel: +34916945561/+34916942861
E-Mails: empresa@faytexsl.com / empresa@fyt.es
Web: www.faytexsl.com / www.fyt.es

# Annex 1: Product data sheet

## Stainless

### 02163N42 i-FYT DK3N 4,2

| | | | |
|---|---|---|---|
| Material | AISI 304 stainless steel | Diameter (mm) | 4,2 |
| Heat treatment | Not hardened | Drilling capacity | 3.5 mm aluminium |
| Corrosion protection | A2 stainless steel | Hardness – Surface | - |
| Lengths (mm) | 14 - 50 | Hardness – Core | - |
| Shear failure load | 4.500 N | Tensile failure load | 7.500 N |

### Maximum pull-out force in aluminium (N)*

| Thickness (mm) | 2,00 | 3,00 | 3,50 |
|---|---|---|---|
| Force (N) | 930 | 1.550 | 1.980 |

*. Mean test value.




### Maximum pull-over force (N)*

| Thickness (mm) | 0,50 | 0,60 | 0,70 | 0,80 | 1,00 |
|---|---|---|---|---|---|
| Without washer (N) | 840 | 1.008 | 1.176 | 1.344 | 1.680 |

*. Values obtained from the Spanish structural steel code for an ST37 sheet (350 N/mm2)



### Maximum shear force (N)

| Thickness (mm) | 1,00 | 1,50 |
|---|---|---|
| Section (mm) | 1,00 | 1,50 |
| Force (N) | 1.479 | 2.169 |

*. Values obtained from the Spanish structural steel code for an ST37 sheet (350 N/mm2)

**Stainless**

www.faytexsl.com · C/ Palier, 19 · 28914 Leganés (Madrid) Spain · ☎ +34 916 945 561

Translation of the Spanish version; it may contain errors.

**Faytex, S.L./Fijaciones FYT, S.L.**
C/ Palier, 19 28914 Leganés (Madrid) Spain
Tel: +34916945561/+34916942861
E-Mails: empresa@faytexsl.com / empresa@fyt.es
Web: www.faytexsl.com / www.fyt.es