Translation of the Spanish version; it may contain errors. The Spanish version prevails.

DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) No 305/2011 (Construction Products Regulation)

No.: FYT-10163N39

1-	Unique identification code of the product-type:	10163N39
2-	Identification of the construction product:	See product label
3-	Intended use of the product:	Drilling and fixing steel sections up to a total thickness of 2.5 mm.
4-	Manufacturer's name and contact address	Fijaciones FYT, S.L. C/ Palier, 19 28914 Leganés (Madrid) Spain
5-	System of assessment and verification of constancy of performance of the product as set out in Annex V	4
6-	European Technical Assessment name and number	Not applicable
7-	Declared performance	

Essential characteristics	Performance	Technical specifications
Dimensions and tolerance	According to technical specifications	DIN 7504N
Ultimate tensile load	See Annex 1	-
Ultimate shear load	See Annex 1	-
Pull-out force	See Annex 1	-
Material	Carbon steel	AISI 1022
Drilling capacity	2,5 mm.	-

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Enrique Capilla, Technical Director

Leganés, 19 November 2026

Faytex, S.L./Fijaciones FYT, S.L.
C/ Palier, 19 28914 Leganés (Madrid) Spain
Tel: +34916945561/+34916942861
E-Mails: empresa@faytexsl.com / empresa@fyt.es
Web: www.faytexsl.com / www.fyt.es

Annex 1: Product data sheet

Zinc-plated

FYT FIJAMOS EL MUNDO

10163N39 FYT DK3N 3,9

Material	AISI 1022 steel		Diameter (mm)	3,9
Heat treatment	Austenitising + quenching + tempering		Drilling capacity	2,5 mm.
Corrosion protection	Zinc-plated - Delta Tone	Hardness	Surface	Min 560 HV
Lengths (mm)	13 - 19		Core	240 - 425 HV
Shear failure load	5.000 N		Tensile failure load	8.500 N



Maximum pull-out force (N)*

Thickness (mm)	1,00	1,50	2,00	2,50	2 x 0,63	2 x 1,00
Force (N)	740	1.346	1.952	2.558	942	1.683


*. Mean test value.



Maximum pull-over force (N)*

Thickness (mm)	0,50	0,60	0,70	0,80	1,00
Without washer (N)	840	1.008	1.176	1.344	1.680
P 16 washer (N)	1.120	1.344	1.568	1.792	2.240
P 18 washer (N)	1.260	1.512	1.764	2.016	2.520

*. Values obtained from the Spanish structural steel code for an ST37 sheet (350 N/mm2)





Maximum shear force (N)

Thickness (mm)	0,63	0,63	0,75	1,00
Section (mm)	2 x 0,63	2,00	1,50	2 x 1,00
Force (N)	1.211	1.817	2.154	2.221

*. Values obtained from the Spanish structural steel code for an ST37 sheet (350 N/mm2)



Zinc-plated

www.faytexsl.com C/ Palier, 19 · 28914 Leganés (Madrid) Spain ☎ +34 916 945 561

Translation of the Spanish version; it may contain errors.

Faytex, S.L./Fijaciones FYT, S.L.
C/ Palier, 19 28914 Leganés (Madrid) Spain
Tel: +34916945561/+34916942861
E-Mails: empresa@faytexsl.com / empresa@fyt.es
Web: www.faytexsl.com / www.fyt.es